



Glass Edge and Surface Mounted

Note

Only for light strips with max. 7.5 W per meter (2.28 W per foot)



Mounting Bracket

Material: Stainless Steel

Color	Item No.
silver colored	833.74.893

Glass Edge Profile

- For glass thickness 4-8 mm (5/32" - 5/16")
 - Without load bearing function
 - Only for 12V LEDs
- L x W x H: 2000 x 28 x 22 mm (78 3/4" x 1 1/8" x 7/8")

Material: Plastic; Cover: milk

Color	Item No.
silver colored	833.74.733

Profile, surface mounted

L x W x H: 2500 x 18 x 12.5 mm (98 3/8" x 3/4" x 1/2")

Material: Aluminum; Cover: milk

Color	Item No.
silver colored anodized	833.74.835

Note

Not suitable for LED 3028.

LED 3015/3028 are not rated for continuous duty (< 8 hrs).



End Cap Set

Material: Plastic ABS

Color	Item No.
silver colored	833.74.877

Supplied With

- 5 sets
- Mounting screws



Door Sensor 12 V

Material: Plastic

Color	Light	Item No.
silver colored	2029/2037	833.89.110



Motion Detector 12 V

- Delay time: 30 sec.
- Detection range: 0-3000 mm

Material: Plastic

Color	Light	Item No.
silver colored	2029/2037	833.89.088



Door Sensor 24 V

Material: Plastic

Color	Light	Item No.
silver colored	3015	833.89.111



Motion Detector 24 V

- Delay time: 30 sec.
- Detection range: 0-3000 mm

Material: Plastic

Color	Light	Item No.
silver colored	3015	833.89.089

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate